




504-362-0781 or 800-889-0781
2236 Manhattan Blvd. Harvey, LA 70058 Fax: 504-367-4216

7x19 Stainless Steel Cable



7 x 19



7 x 19

*Listed for comparison only. Actual operating loads may vary, but should never exceed recommended design factor or 20% of catalog Breaking Strength.

** According to Federal Specifications RR-W-410D.

Meeting dimensional and strength requirements of MIL-W-83420E.

Size	Approx. Wt. per 1000 Ft. in Pounds	Breaking Strength in Pounds*
Size	Approx. Wt. per 1000 Ft. in Pounds	Breaking Strength in Pounds*
3/32" ** 17		920
1/8" ** 29		1,760
5/32" ** 45		2,400
3/16" ** 65		3,700
7/32" ** 86		5,000
1/4" ** 110		6,400
5/16" ** 173		9,000
3/8" ** 243		12,000
Size	Approx. Wt. per 1000 Ft. in Pounds	Breaking Strength in Pounds*
Size	Approx. Wt. per 1000 Ft. in Pounds	Breaking Strength in Pounds*
1/16" (7x7) 7.5		480
1/8" 29		1,670
3/16" 65		3,565
1/4" 110		5,875
5/16" 173		8,825
3/8" 243		11,760
